Listing of the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

- 1. **(Previously presented)** A method comprising orienting in the machine direction (MD) a high density polyethylene blown film to a draw-down ratio greater than 10:1 to produce an MD oriented film having a 1% secant MD modulus of 1,000,000 psi or greater.
- 2. **(Original)** The method of claim 1 wherein the MD oriented film has a 1% secant transverse-direction (TD) modulus of 300,000 psi or greater.
- 3. **(Original)** The method of claim 1 wherein the blown film is made from a polyethylene resin which has a density within the range of 0.950 to 0.970 g/cc.
- 4. **(Original)** The method of claim **1** wherein the blown film is made from a polyethylene resin which has a density within the range of 0.955 to 0.965 g/cc.
- 5. **(Original)** The method of claim 1 wherein the blown film is made from a polyethylene resin which has a density within the range of 0.958 to 0.962 g/cc.
- 6. **(Original)** The method of claim 1 wherein the blown film is made from a polyethylene resin which has a weight average molecular weight (Mw) within the range of 130,000 to 1,000,000.
- 7. **(Original)** The method of claim **6** wherein the Mw is within the range of 150,000 to 500,000.
- 8. **(Original)** The method of claim **6** wherein the Mw is within the range of 155,000 to 300,000.
- 9. **(Original)** The method of claim **6** wherein the Mw is within the range of 155,000 to 250,000.

- 10. **(Original)** The method of claim 1 wherein the blown film is made from a polyethylene resin which has a number average molecular weight (Mn) within the range of 10,000 to 500,000.
- 11. **(Original)** The method of claim **10** wherein the Mn is within the range of 11,000 to 100,000.
- 12. **(Original)** The method of claim **10** wherein the Mn is within the range of 11,000 to 50,000.
- 13. **(Original)** The method of claim **10** wherein the Mn is within the range of 11,000 to 20,000.
- 14. (Original) The method of claim 1 wherein the draw-down ratio is 11:1 or greater.
- 15. **(Original)** The method of claim 1 wherein the oriented film having a 1% secant MD modulus of 1,100,000 psi or greater.

Claims 16-19 are withdrawn for consideration due to the Examiner's restriction requirement.